

LONDON FOGGERS

Used everywhere in the world
since 1968



NEW
4 cycle
Subaru Engine

COLT4

Portable ULV for indoor and outdoor application

Specifications

Engine	Air Cooled, 4 stroke, single cylinder. regular gasoline ONLY
Fuel Tank	20 Ounces, (.65 liters) (30-45 minute run time)
Compressor	Rotary, oil-less, 100% ball and roller bearing, graphite fins
Formulation Tank	One quart, 32 ounces (.946 L)
Formulation Output	Siphon nozzle with 3 orifice discs included
Formula Metering	Various orifices discs 3 sizes included
Particle Size	90% less than 15 microns
Weight	20.2 lbs dry (9.2 kg)
Length	14" (35.6 cm)
Width	11.5" (29.2 cm)
Height	13.5" (34.3 cm)

Colt produces a true ULV droplet size, 90% of the droplets are less than 15 microns in diameter. This is the recommended flow rates with Malathion!

The Colt is a light weight compact design, weighing only 20 pounds with dimensions of 13.5" long X 12" wide and 13" tall. The Colt is equipped with a heavy duty shoulder strap for the operators comfort. All components are selected for longevity and reliability. Finger tip controls offer simple and convenient operation along with a NEW 4 cycle engine, which requires no mixing of the oil and gas. The 4 cycle engine is both powerful and very easily started. The flow rates can be adjusted for various materials or applications by changing an orifice disk with differing amounts of flow. The Colt can atomize both oil or water based products. Tested with a laser based atomizer, the Colt passes droplet tests with flying colors, and the new engine is just what you asked for, no mixing of the oil and gas!



Easy to grip handle

505 Brimhall Avenue
Long Lake, MN 55356

P. 952-473-5366

F. 952-473-5302

TF. 800-448-8525

E. salesupport@londonfoggers.com



*Used everywhere
in the world*

www.londonfoggers.com

© Copyright London Foggers 2010. All Rights Reserved